

[Create Email/Fax Request](#)

apps.barnesdistribution.com

Click [here](#) to go back to MSDS



Barnes Distribution

**1301 E. 9th Street, #700
Cleveland OH 44114
(800) 726-9626**



Material Safety Data Sheet

MSDS Form No. : 005693

Item No. : 03060

CRC (R*)

MATERIAL SAFETY DATA SHEET

-----SECTION 1: PRODUCT & COMPANY IDENTIFICATION -----

PRODUCT NAME: SCREWLOOSE (R*) INDUSTRIAL PENETRATING OIL (AEROSOL)

PRODUCT NUMBER(S): 03059, 03060, 83060

MANUFACTURED BY:

CRC INDUSTRIES, INC.
885 LOUIS DRIVE
WARMINSTER, PA 18974

WWW.CRCINDUSTRIES.COM

GENERAL INFORMATION: (215) 674-4300

TECHNICAL ASSISTANCE: (800) 521-3168

CUSTOMER SERVICE: (800) 272-4620

24-HR EMERGENCY (CHEMTREC): (800) 424-9300

-----SECTION 2: HAZARDS IDENTIFICATION -----

EMERGENCY OVERVIEW:

APPEARANCE & ODOR: LIGHT AMBER LIQUID, PETROLEUM SOLVENT ODOR

DANGER:

FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. CONTENTS UNDER PRESSURE.

AS DEFINED BY OSHA'S HAZARD COMMUNICATION STANDARD, THIS PRODUCT IS HAZARDOUS.

POTENTIAL HEALTH EFFECTS:

EYE:

MAY CAUSE MILD EYE IRRITATION. SYMPTOMS INCLUDE STINGING, TEARING AND REDNESS.

SKIN:

CAN CAUSE SKIN IRRITATION. PROLONGED OR REPEATED CONTACT MAY DRY THE SKIN. SYMPTOMS MAY INCLUDE REDNESS, BURNING, DRYING, AND CRACKING OF THE SKIN.

INHALATION:

EXPECTED TO HAVE A LOW DEGREE OF TOXICITY BY INHALATION. BREATHING CONCENTRATED VAPORS MAY BE HARMFUL. SYMPTOMS OF OVEREXPOSURE INCLUDE IRRITATION OF THE NOSE AND THROAT, HEADACHE, DIZZINESS, DROWSINESS, LOSS OF COORDINATION AND OTHER SIGNS OF CENTRAL NERVOUS SYSTEM DEPRESSION.

INGESTION:

LOW DEGREE OF TOXICITY BY INGESTION. MAY CAUSE IRRITATION OF DIGESTIVE TRACT, NAUSEA AND VOMITING. MAIN HAZARD IS ASPIRATION OF MATERIAL INTO LUNGS DURING SWALLOWING OR VOMITING. THIS CAN LEAD TO LUNG INFLAMMATION AND DAMAGE.

CHRONIC EFFECTS:

REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

TARGET ORGANS: KIDNEYS, CENTRAL NERVOUS SYSTEM.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

SKIN DISORDERS, RESPIRATORY DISORDERS

SEE SECTION 11 FOR TOXICOLOGY AND CARCINOGENICITY INFORMATION ON PRODUCT INGREDIENTS.

-----SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS -----

COMPONENT	CAS NUMBER	% BY WT.
STODDARD SOLVENT	8052-41-3	45 - 55
HYDROTREATED LIGHT DISTILLATES	64742-47-8	35 - 45
SOLVENT REFINED HEAVY PARAFFINIC DISTILLATES	64741-88-4	5 - 10
OLEIC ACID	112-80-1	1 - 5
CARBON DIOXIDE	124-38-9	1 - 5

-----SECTION 4: FIRST AID MEASURES -----

EYE CONTACT:

IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. CALL A PHYSICIAN IF

IRRITATION PERSISTS.

SKIN CONTACT:

REMOVE CONTAMINATED CLOTHING AND WASH AFFECTED AREA WITH SOAP AND WATER. CALL A PHYSICIAN IF IRRITATION PERSISTS. WASH CONTAMINATED CLOTHING PRIOR TO RE-USE.

INHALATION:

REMOVE PERSON TO FRESH AIR. KEEP PERSON CALM. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT GIVE OXYGEN. CALL A PHYSICIAN.

INGESTION:

DO NOT INDUCE VOMITING. CONTACT A PHYSICIAN IMMEDIATELY. IF VICTIM IS DROWSY OR UNCONSCIOUS, PLACE INDIVIDUAL ON THE LEFT SIDE WITH HEAD DOWN.

NOTE TO PHYSICIANS:

THIS MATERIAL IS AN ASPIRATION HAZARD. POTENTIAL DANGER FROM ASPIRATION MUST BE WEIGHED AGAINST POSSIBLE ORAL TOXICITY WHEN DECIDING WHETHER TO INDUCE VOMITING.

-----SECTION 5: FIRE-FIGHTING MEASURES -----

FLAMMABLE PROPERTIES:

THIS PRODUCT IS FLAMMABLE IN ACCORDANCE WITH AEROSOL FLAMMABILITY DEFINITIONS (16 CFR 1500.3(C)(6)).

FLASH POINT: 109 F (TCC)

AUTOIGNITION TEMPERATURE: ND

UPPER EXPLOSIVE LIMIT: 6.0 (EST)

LOWER EXPLOSIVE LIMIT: 1.0 (EST)

SUITABLE EXTINGUISHING MEDIA:

FOAM, CARBON DIOXIDE, DRY CHEMICAL; CLASS B FIRE EXTINGUISHERS

PRODUCTS OF COMBUSTION: OXIDES OF CARBON

PROTECTION OF FIRE-FIGHTERS:

FIREFIGHTERS SHOULD WEAR SELF-CONTAINED, NIOSH-APPROVED BREATHING APPARATUS FOR PROTECTION AGAINST SUFFOCATION AND POSSIBLE TOXIC DECOMPOSITION PRODUCTS. PROPER EYE AND SKIN PROTECTION SHOULD BE PROVIDED. USE WATER SPRAY TO KEEP FIRE-EXPOSED CONTAINERS COOL AND TO KNOCK DOWN VAPORS WHICH MAY RESULT FROM PRODUCT DECOMPOSITION.

-----SECTION 6: ACCIDENTAL RELEASE MEASURES -----

PERSONAL PRECAUTIONS: USE PERSONAL PROTECTION RECOMMENDED IN SECTION 8.

ENVIRONMENTAL PRECAUTIONS:

TAKE PRECAUTIONS TO PREVENT CONTAMINATION OF GROUND AND SURFACE WATERS. DO NOT FLUSH INTO SEWERS OR STORM DRAINS.

METHODS FOR CONTAINMENT & CLEAN-UP:

DIKE AREA TO CONTAIN SPILL. VENTILATE THE AREA WITH FRESH AIR. IF IN CONFINED SPACE OR LIMITED AIR CIRCULATION AREA, CLEAN-UP WORKERS SHOULD WEAR APPROPRIATE RESPIRATORY PROTECTION. RECOVER OR ABSORB SPILLED MATERIAL USING AN ABSORBENT DESIGNED FOR CHEMICAL SPILLS. PLACE USED ABSORBENTS INTO PROPER WASTE CONTAINERS.

-----SECTION 7: HANDLING AND STORAGE -----

HANDLING PROCEDURES:

DO NOT USE NEAR SOURCES OF IGNITION. DO NOT USE ON ENERGIZED EQUIPMENT. USE WITH PROPER VENTILATION. WASH HANDS AFTER USE AND BEFORE HANDLING FOOD.

STORAGE PROCEDURES:

STORE IN A COOL DRY AREA OUT OF DIRECT SUNLIGHT. AEROSOL CANS MUST BE MAINTAINED BELOW 120 F TO PREVENT CANS FROM RUPTURING.

AEROSOL STORAGE LEVEL: III

-----SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION -----

EXPOSURE GUIDELINES:

COMPONENT	OSHA		ACGIH		OTHER		UNIT
	TWA	STEL	TWA	STEL	TWA	SOURCE	
STODDARD SOLVENT	500	NE	100	NE	NE		PPM
HYDROTREATED LIGHT DISTILLATES	NE	NE	NE	NE	NE		
SOLVENT REFINED HEAVY PARAFFINIC DISTILLATES	NE	NE	NE	NE	NE		
OLEIC ACID	NE	NE	NE	NE	NE		
CARBON DIOXIDE	5000	NE	5000	30000	NE		PPM

N.E.: NOT ESTABLISHED

(C): CEILING

(S): SKIN

(V): VACATED

ENGINEERING CONTROLS:

AREA SHOULD HAVE VENTILATION TO PROVIDE FRESH AIR. LOCAL EXHAUST VENTILATION IS GENERALLY PREFERRED BECAUSE IT CAN CONTROL THE EMISSIONS OF THE CONTAMINANT AT THE SOURCE, PREVENTING DISPERSION INTO THE GENERAL WORK AREA. USE MECHANICAL MEANS IF NECESSARY TO MAINTAIN VAPOR LEVELS BELOW THE EXPOSURE GUIDELINES. IF WORKING IN A CONFINED SPACE, FOLLOW APPLICABLE OSHA REGULATIONS.

RESPIRATORY PROTECTION:

NONE REQUIRED FOR NORMAL WORK WHERE ADEQUATE VENTILATION IS PROVIDED. IF ENGINEERING CONTROLS ARE NOT FEASIBLE OR IF EXPOSURE EXCEEDS THE APPLICABLE EXPOSURE LIMITS, USE A NIOSH-APPROVED CARTRIDGE RESPIRATOR WITH ORGANIC

VAPOR CARTRIDGE. USE A SELF-CONTAINED BREATHING APPARATUS IN CONFINED SPACES AND FOR EMERGENCIES.

EYE/FACE PROTECTION:

FOR NORMAL CONDITIONS, WEAR SAFETY GLASSES. WHERE THERE IS REASONABLE PROBABILITY OF LIQUID CONTACT, WEAR SPLASH-PROOF GOGGLES.

SKIN PROTECTION:

USE PROTECTIVE GLOVES SUCH AS NITRILE OR NEOPRENE. ALSO, USE FULL PROTECTIVE CLOTHING IF THERE IS PROLONGED OR REPEATED CONTACT OF LIQUID WITH SKIN.

-----SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES -----

PHYSICAL STATE: LIQUID

COLOR: LIGHT AMBER

ODOR: PETROLEUM SOLVENT

SPECIFIC GRAVITY: 0.790

INITIAL BOILING POINT: 300 F

FREEZING POINT: ND

VAPOR PRESSURE: ND

VAPOR DENSITY (AIR = 1): >4

EVAPORATION RATE (BUTYL ACETATE = 1): <1

SOLUBILITY: INSOLUBLE IN WATER

pH: NA

VOLATILE ORGANIC COMPOUNDS:

WT %: 48.4

G/L: 382.4

LBS./GAL: 3.19

-----SECTION 10: STABILITY AND REACTIVITY -----

STABILITY: STABLE

CONDITIONS TO AVOID: SOURCES OF IGNITION; TEMPERATURE EXTREMES

INCOMPATIBLE MATERIALS: STRONG OXIDIZING AGENTS

HAZARDOUS DECOMPOSITION PRODUCTS: OXIDES OF CARBON

POSSIBILITY OF HAZARDOUS REACTIONS: NO

-----SECTION 11: TOXICOLOGICAL INFORMATION -----

LONG-TERM TOXICOLOGICAL STUDIES HAVE NOT BEEN CONDUCTED FOR THIS PRODUCT. THE FOLLOWING INFORMATION IS AVAILABLE FOR COMPONENTS OF THIS PRODUCT.

ACUTE EFFECTS:

COMPONENT	TEST	RESULT	ROUTE	SPECIES
HYDROTREATED LIGHT DISTILLATE	LD50	>5 G/KG	ORAL	RAT
HYDROTREATED LIGHT DISTILLATE	LD50	>2 G/KG	DERMAL	RABBIT
HYDROTREATED LIGHT DISTILLATE	LC50	>5 MG/L/4H	INHALATION	RAT

CHRONIC EFFECTS:

CARCINOGENICITY:

	COMPONENT	RESULT
OSHA	NONE LISTED	
IARC	NONE LISTED	
NTP	NONE LISTED	

MUTAGENICITY: NO INFORMATION AVAILABLE

OTHER: NONE

-----SECTION 12: ECOLOGICAL INFORMATION -----

ECOLOGICAL STUDIES HAVE NOT BEEN CONDUCTED FOR THIS PRODUCT. THE FOLLOWING INFORMATION IS AVAILABLE FOR COMPONENTS OF THIS PRODUCT.

ECOTOXICITY: NO INFORMATION AVAILABLE

PERSISTENCE / DEGRADABILITY: NO INFORMATION AVAILABLE

BIOACCUMULATION / ACCUMULATION: NO INFORMATION AVAILABLE

MOBILITY IN ENVIRONMENT: NO INFORMATION AVAILABLE

-----SECTION 13: DISPOSAL CONSIDERATIONS -----

DISPOSAL:

THE DISPENSED LIQUID PRODUCT IS A RCRA HAZARDOUS WASTE FOR THE CHARACTERISTIC OF IGNITABILITY WITH A WASTE CODE OF D001. (SEE 40 CFR PART 261.20 - 261.33)

AEROSOL CONTAINERS SHOULD BE EMPTIED AND DEPRESSURIZED BEFORE DISPOSAL. EMPTY CONTAINERS MAY BE RECYCLED.

ALL DISPOSAL ACTIVITIES MUST COMPLY WITH FEDERAL, STATE AND LOCAL REGULATIONS. LOCAL REGULATIONS MAY BE MORE STRINGENT THAN STATE OR NATIONAL REQUIREMENTS.

-----SECTION 14: TRANSPORT INFORMATION -----

PROPER SHIPPING DESCRIPTION:

US DOT (GROUND): CONSUMER COMMODITY, ORM-D

SPECIAL PROVISIONS: NONE

-----SECTION 15: REGULATORY INFORMATION -----

U.S. FEDERAL:

TOXIC SUBSTANCES CONTROL ACT (TSCA):

ALL INGREDIENTS ARE EITHER LISTED ON THE TSCA INVENTORY OR ARE EXEMPT.

COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION AND LIABILITY ACT (CERCLA):

REPORTABLE QUANTITIES (RQ'S) EXIST FOR THE FOLLOWING INGREDIENTS: NONE

SPILLS OR RELEASES RESULTING IN THE LOSS OF ANY INGREDIENT AT OR ABOVE ITS RQ REQUIRE IMMEDIATE NOTIFICATION TO THE NATIONAL RESPONSE CENTER (800-424-8802) AND TO YOUR LOCAL EMERGENCY PLANNING COMMITTEE.

SUPERFUND AMENDMENTS REAUTHORIZATION ACT (SARA) TITLE III:

SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES (EHS): NONE

SECTION 311/312 HAZARD CATEGORIES:

FIRE HAZARD: YES

REACTIVE HAZARD: NO

RELEASE OF PRESSURE: YES

ACUTE HEALTH HAZARD: YES

CHRONIC HEALTH HAZARD: NO

SECTION 313 TOXIC CHEMICALS:

THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372: NONE

CLEAN AIR ACT:

SECTION 112 HAZARDOUS AIR POLLUTANTS (HAPS): NONE

STATE REGULATIONS:

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROP 65):

THIS PRODUCT MAY CONTAIN THE FOLLOWING CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM: NONE

STATE RIGHT TO KNOW:

NEW JERSEY: 8052-41-3, 124-38-9, 112-80-1

PENNSYLVANIA: 8052-41-3, 124-38-9, 112-80-1

MASSACHUSETTS: 8052-41-3, 124-38-9, 112-80-1
RHODE ISLAND : 8052-41-3, 124-38-9, 112-80-1

ADDITIONAL REGULATORY INFORMATION:

THIS PRODUCT COMPLIES WITH CONSUMER PRODUCT VOC REGULATIONS AS A PENETRANT.

-----SECTION 16: OTHER INFORMATION -----

NFPA:

HEALTH 1
FLAMMABILITY 2
REACTIVITY 0

HMIS:

HEALTH 1
FLAMMABILITY 2
REACTIVITY 0
PPE B

PREPARED BY: MICHELLE RUDNICK

CRC #: 575G

REVISION DATE: 09/15/2010

CHANGES SINCE LAST REVISION:

SECTION 9: REDUCED VOC CONTENT

THE INFORMATION CONTAINED IN THIS DOCUMENT APPLIES TO THIS SPECIFIC MATERIAL AS SUPPLIED. IT MAY NOT BE VALID FOR THIS MATERIAL IF IT IS USED IN COMBINATION WITH ANY OTHER MATERIALS. THIS INFORMATION IS ACCURATE TO THE BEST OF CRC INDUSTRIES' KNOWLEDGE OR OBTAINED FROM SOURCES BELIEVED BY CRC TO BE ACCURATE. BEFORE USING ANY PRODUCT, READ ALL WARNINGS AND DIRECTIONS ON THE LABEL.

CAS: CHEMICAL ABSTRACT SERVICE

PPM: PARTS PER MILLION

TCC: TAG CLOSED CUP

PMCC: PENSKY-MARTENS CLOSED CUP

PPE: PERSONAL PROTECTION EQUIPMENT

TWA: TIME WEIGHTED AVERAGE

OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

ACGIH: AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS

NIOSH: NATIONAL INSTITUTE OF OCCUPATIONAL SAFETY & HEALTH

NA: NOT APPLICABLE

ND: NOT DETERMINED

NE: NOT ESTABLISHED

G/L: GRAMS PER LITER

LBS./GAL: POUNDS PER GALLON

STEL: SHORT TERM EXPOSURE LIMIT