



MULTI FITTINGS

MATERIAL SAFETY DATA SHEET

SECTION 1. PRODUCT IDENTIFICATION

MATERIAL NAME: PVC Pipe and Fittings

PRODUCT USE: Water, sewer, conduit, duct and industrial piping

SECTION 2. PREPARATION INFORMATION

<u>MANUFACTURER/SUPPLIER:</u>	IPEX Inc. 50 Valleybrook Drive Don Mills, Ontario Canada M3B 2S9	<u>TELEPHONE NO.:</u>	(416) 445-3400
		<u>PREPARED BY:</u>	Health, Safety and Environment
		<u>DATE PREPARED:</u>	January 13, 2010

SECTION 3. HAZARDOUS INGREDIENTS

This is not a "controlled product" under the Hazardous Products Act. PVC is inert in all intended applications.

INGREDIENT NAME	CAS NUMBER	APPROXIMATE CONCENTRATION %	LD ₅₀ /LC ₅₀	EXPOSURE LIMIT TLV ACGIH mg/m ³
PVC Resin Blend	Not applicable	100%	Not available	Not available

SECTION 4. PHYSICAL DATA

PHYSICAL STATE:	Solid
ODOUR AND APPEARANCE:	White, blue, green, grey or orange, odourless
BOILING POINT:	385°F (196°C)
FREEZING POINT:	Not applicable
VAPOUR PRESSURE:	Not applicable
VAPOUR DENSITY:	Not applicable
SPECIFIC GRAVITY:	1.4 – 1.65
pH:	Not applicable
ODOUR THRESHOLD:	Not applicable
EVAPORATION RATE:	Not applicable
COEFFICIENT WATER/OIL DISTR:	Not applicable

MSDS: PVC Pipe and Fittings	Revision Level: # 4	Prepared Date: Jan 13, 2010	Page 1 of 4
Prepared by: Amy Slattery	Checked by: Stan Rodriguez	Approved by:	



SECTION 5. FIRE OR EXPLOSION HAZARD

FIRE FIGHTING:	Wear self-contained breathing apparatus (SCBA) equipped with a full face piece and operated in a pressure-demand mode or other positive-pressure mode and protective clothing. Personnel not having suitable respiratory protection must leave the area to prevent significant exposure to toxic gases from combustion, burning, or decomposition. In an enclosed or poorly ventilated area, wear SCBA during cleanup immediately after a fire as well as during the attack phase of fire fighting operations. Run off water from fire fighting may have corrosive effects.
EXTINGUISHING MEDIA:	Water spray, carbon dioxide, foam, dry chemical
HAZARDOUS COMBUSTION PRODUCTS:	Hydrogen Chloride, Carbon Dioxide, Carbon Monoxide, other substances dependent on fire conditions
FLASH POINT:	734°F (390°C) approx.
LOWER FLAMMABLE LIMIT:	Not applicable.
UPPER FLAMMABLE LIMIT:	Not applicable.
AUTOIGNITION:	800°F (425°C) (ASTM D-1929) approx.
CONDITIONS OF FLAMMABILITY:	Only if highly heated and exposed to a continuous source of ignition. PVC pipe will not support combustion.
IMPACT SENSITIVITY:	Not available
STATIC DISCHARGE:	Not available

SECTION 6. REACTIVITY DATA

STABILITY:	Not available.
REACTIVITY:	Not available
INCOMPATIBILITY WITH OTHER SUBSTANCES:	Not available
HAZARDOUS DECOMPOSITION:	See section 5

SECTION 7. TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO PRODUCT:	No acute health effects reported with the inhalation of PVC dust; dust may irritate the eyes.
EFFECTS OF CHRONIC EXPOSURE TO PRODUCT:	Vinyl resin is not known to cause any disease. Dust exposure should always be minimized. Routine inhalation of dust of any kind should be

MSDS: PVC Pipe and Fittings	Revision Level: # 4	Prepared Date: Jan 13, 2010	Page 2 of 4
Prepared by: Amy Slattery	Checked by: Stan Rodriguez	Approved by:	



avoided. Exercise care when dumping bags, sweeping, mixing or doing other tasks which can create dust.

ROUTES OF ENTRY:	Inhalation, eye contact with dust (only when cutting or grinding)
SENTITIZATION:	None known
IRRITANCY:	Not available
CHRONIC/CARCINOGENICITY:	Not available
REPRODUCTIVE TOXICITY:	Not available
TERATOGENICITY:	Not available
MUTAGENICITY:	Not available
TOXICOLOGICALLY SYNERGISTIC PRODUCTS:	Not available

SECTION 8. PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT TO BE USED:	When cutting, the use of eye protection and a NIOSH-approved respirator for dust is recommended.
ENGINEERING CONTROLS TO BE USED:	Ventilate adequately when cutting.
WASTE DISPOSAL:	Handle in accordance with federal, state, provincial and municipal regulations.
PROCEDURES TO BE FOLLOWED IN CASE OF LEAK OR SPILL:	Pipe fragments and debris should be swept up and removed to a disposal container.
HANDLING PROCEDURES AND EQUIPMENT:	Avoid creating and breathing PVC dust
STORAGE REQUIREMENTS:	None
SPECIAL SHIPPING INFORMATION:	Not applicable

SECTION 9. EMERGENCY AND FIRST AID MEASURES

SPECIFIC FIRST AID MEASURES:	No situation is likely to arise from routine handling of PVC pipes.
EYES:	Remove particles with clean water. If irritation persists, consult a physician.
SKIN:	Wash with soap and water
INGESTION:	Do not induce vomiting; consult a physician.
INHALATION:	If irritation persists, consult a physician

MSDS: PVC Pipe and Fittings	Revision Level: # 4	Prepared Date: Jan 13, 2010	Page 3 of 4
Prepared by: Amy Slattery	Checked by: Stan Rodriguez	Approved by:	



SECTION 10. ADDITIONAL GENERAL INFORMATION

Disclaimer

The information contained in this material safety data sheet is based on information available to IPEX Inc. and is believed to be accurate. Where this information is based on data developed by third parties, IPEX Inc. expressly denies liability. IPEX Inc. makes no warranty, expressed or implied, regarding the accuracy of this information or data or the results obtained from its use. All recommendations are made without guarantee, since the conditions of use of this product are beyond IPEX Inc.'s control. IPEX Inc. assumes no responsibility for any damages resulting from the use of this product described herein.

Please consult IPEX Inc. for further information.

MSDS: PVC Pipe and Fittings	Revision Level: # 4	Prepared Date: Jan 13, 2010	Page 4 of 4
Prepared by: Amy Slattery	Checked by: Stan Rodriguez <i>SR</i>	Approved by: <i>SR</i>	