



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04/17/2014

Version number 4

Revision: 11/20/2012

1 Identification of the substance/mixture and of the company/undertaking

• **Product Identifier**

• **Trade name:** UTP 6820 LC

• **Application of the substance / the mixture** electrodes for welding

• **Details of the supplier of the safety data sheet**

• **Manufacturer/Supplier:**

Boehler Welding Group, Canada Ltd.

1555 Bonhill Road, Unit 11
MISSISSAUGA, ONTARIO L5T 1Y5
CANADA

phone 1 905 564 0589

fax

1 905 564 2027

Member of the BÖHLER-WELDING Group

• **Further information obtainable from:** QS department

• **Emergency telephone number:** Tel: +49 (0) 7633-409-151 (Mo - Do 8-17, Fr 8-13 Uhr)

2 Hazards Identification

• **Classification of the substance or mixture**



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

• **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

General: Different kinds of fume and dust occur during the welding and grinding process. Chromium-VI compounds and nickel oxides might occur, which are classified as carcinogenic. In addition irritant substances such as fluorides and manganese oxides as well as fine dusts (mostly iron oxides) occur. Health Hazards (acute and chronic) Welding electrodes and wires are non-hazardous solids at ambient temperature.

Actual exposure should be determined by monitoring the fume in the operator's breathing zone. Compounds of Chromium and Nickel in the fume should be considered possible carcinogens per OSHA29. CFR 1910. 1200. No clear association, however, has been established between Cr and Ni in welding fume and the development of cancer. Short term overexposure to welding fumes may result in discomfort such as metal fume fever, dizziness, nausea, or dryness or irritation of nose, throat or eyes and may aggravate pre-existing respiratory problems (e.g. asthma, emphysema). Exposure to extremely high levels of fluorides can cause abdominal pain, diarrhea, muscular weakness, and convulsions. In extreme cases it can cause loss of consciousness and death.

Long term overexposure to welding fumes can lead to siderosis (iron deposits in lung) and may affect pulmonary function.

Manganese overexposure can affect the central nervous system, resulting in impaired speech and movement. The primary entry route for welding fumes and gases is by inhalation. Bronchitis and some lung fibrosis have been reported. Repeated exposure to fluorides may cause excessive calcification of the bone and calcification of ligaments of the ribs, pelvis and spinal column. May cause skin rash.

Overexposure to hexavalent chromium and nickel present in welding fume can present the risk of lung cancer, asthma and damage to the nose and skin.

Arc rays can injure eyes and burn skin. Electric shock can kill. Before use, read and understand the manufacturer's instructions, MSDS's and your employer's safety practices. Keep your head out of the

(Contd. on page 2)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04/17/2014

Version number 4

Revision: 11/20/2012

Trade name: UTP 6820 LC

(Contd. of page 1)

fumes. Use enough ventilation, exhaust at the arc, or both, to keep fumes and gases from your breathing zone and the general area. Wear correct eye, ear and body protection. Do not touch live electrical parts. See American National Standard Z49.1, and OSHA Safety and Health Standards.

Carcinogenicity

Nickel: The International Agency for Research on Cancer indicates nickel refining and "certain nickel compounds" were cancer-causing, but could not state with certainty which forms of nickel may be carcinogenic. The National Toxicology Program lists nickel powder, nickel subsulfide, nickel oxide, nickel carbonate, nickel carbonyl and nickelocene as substances "that may reasonably anticipated to be carcinogens". Because of this, the OSHA Hazard Communication Standard requires that everyone who manufactures or imports these substances or mixtures or alloys containing these substances must warn of a cancer hazard on their MSDS's and labels. This warning is mandated by OSHA even though studies have not demonstrated cancer risks associated with the use of nickel. Intramuscular injection and implantation of nickel powder produced localized tumors in rats and mice. Inhalation studies using animals showed no evidence of carcinogenicity.

Chromium: The International Agency for Research on Cancer and the National Toxicology Program indicates there is sufficient evidence for carcinogenicity of Chromium compounds both in humans and experimental animals. IARC notes that "the compounds responsible for the carcinogenic effect in humans cannot be specified". Studies with chromium metal and trivalent forms of chromium compounds have shown inadequate evidence for carcinogenicity in both animals and humans.

Threshold Limit Value: The ACGIH recommended general limit for Welding Fume NOC-(Not Otherwise Classified) is 5 mg/m³. The TLV-TWA is the time weighted average concentration for a normal 8-hour workday and a 40-hour workweek, to which nearly all workers may be repeatedly exposed, day after day, without adverse effect. Limit Values are figures published by the American Conference of Government Industrial Hygienists.

Workers exposed to hexavalent chrome (Cr+6) are at an increased risk of developing lung cancer. It is also possible that occupational exposure to (Cr+6) may result in asthma and damage to the nasal epithelia and skin. To avoid any risk follow the requirements of the OSHA rule for hexavalent chromium published on February 28, 2006 in the U.S. Federal register 71, pages: 10099-10385 which established an 8-hour time-weighted average (TWA) exposure limit of 5 micrograms of hexavalent chrome per cubic meter of air (5 µg/m³).

Crystalline silica: The National Toxicology Program indicates there is sufficient evidence for the carcinogenicity or respirable crystalline silica in experimental animals. Increases in incidence of lung cancers have been found in inhalation studies in rats. An IARC working group reported there is limited evidence for the carcinogenicity of crystalline silica in humans.

Other precautions: Electric shock from arc welding equipment can kill. When welding arc or torch flame may be a source of ignition of combustible.

• Label elements

• Labelling according to EU guidelines:

The product is not subject to identification regulations under EU Directives and the Ordinance on Hazardous Materials (German GefStoffV).

• Hazard-determining components of labelling:

nickel

• Special labelling of certain preparations:

Contains nickel, cobalt. May produce an allergic reaction.

• Other hazards

• Results of PBT and vPvB assessment

• PBT: Not applicable.

(Contd. on page 3)

CA

**Safety data sheet**
according to 1907/2006/EC, Article 31

Printing date 04/17/2014

Version number 4

Revision: 11/20/2012

Trade name: UTP 6820 LC

· vPvB: Not applicable.

(Contd. of page 2)

3 Composition/Information on Ingredients· **Chemical characterization: Mixtures**· **Description:** Mixture of substances listed below with nonhazardous additions.· **Dangerous components:**

| | | |
|--------------------------------------|--|---------|
| CAS: 7440-47-3 EINECS: 231-157-5 | chromium | 10-25% |
| CAS: 13463-67-7 EINECS: 236-675-5 | titanium dioxide | 10-25% |
| CAS: 7440-02-0 EINECS: 231-111-4 | nickel T R48/23; Xn R40; Xi R43 Carc. Cat. 3 Carc. 1A, H350; Skin Sens. 1, H317 | 2.5-10% |
| CAS: 471-34-1 EINECS: 207-439-9 | calcium carbonate | 2.5-10% |
| CAS: 7439-96-5 EINECS: 231-105-1 | manganese Xn R20-48 Acute Tox. 4, H332 | ≤ 2.5% |

· **Additional information:**

Warning: This product contains or produces a chemical known to the state of California to cause cancer.

| | | | |
|-------------------------------------|--------------------------------------|--------------------|---------|
| CAS: 7439-89-6 EINECS: 231-096-4 | iron | | 25-50% |
| CAS: 12068-56-3 | Aluminiumsilikate | | 2.5-10% |
| CAS: 68476-25-5 | Feldspat | | 2.5-10% |
| CAS: 7631-86-9 EINECS: 231-545-4 | silicon dioxide, chemically prepared | Acute Tox. 1, H300 | ≤ 2.5% |

4 First aid measures· **Description of first aid measures**· **General information:** No special measures required.· **After inhalation:** Supply fresh air; consult doctor in case of complaints.· **After skin contact:** If skin irritation continues, consult a doctor.· **After eye contact:** Rinse opened eye for several minutes under running water.· **After swallowing:** If symptoms persist consult doctor.· **Information for doctor:**· **Most important symptoms and effects, both acute and delayed**

No further relevant information available.

(Contd. on page 4)

CA



voestalpine Böhler Welding

Page 4/9

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04/17/2014

Version number 4

Revision: 11/20/2012

Trade name: UTP 6820 LC

(Contd. of page 3)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:** Pick up mechanically.
- **Reference to other sections** No dangerous substances are released.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Prevent formation of dust.
- **Information about fire - and explosion protection:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:**
Ventilation: Use enough ventilation, local exhaust at the arc, or both, to keep the fumes and gases from the worker's breathing zone and the general area. Train the welder to keep his head out of the fumes. Keep exposures as low as possible
Respiratory Protection: Use respirable fumes respirator or air supplied respirator when welding in confined space or where local exhaust or ventilation does not keep exposure below the recommended exposure limit.

· **Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

7440-47-3 chromium

PEL (USA) 1 mg/m³

REL (USA) 0.5 mg/m³

(Contd. on page 5)

CA



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04/17/2014

Version number 4

Revision: 11/20/2012

Trade name: UTP 6820 LC

(Contd. of page 4)

| | |
|------------------------------------|--|
| TLV (USA) | 0.5 mg/m ³ |
| 13463-67-7 titanium dioxide | |
| PEL (USA) | 15* mg/m ³ *Total dust |
| REL (USA) | Lowest feasible conc.; (LOQ 0.2 mg/m ³) |
| TLV (USA) | 10 mg/m ³ |
| 7440-02-0 nickel | |
| PEL (USA) | 1 mg/m ³ |
| REL (USA) | 0.015 mg/m ³ |
| TLV (USA) | 1.5 l mg/m ³ |
| 471-34-1 calcium carbonate | |
| PEL (USA) | 15*; 5** mg/m ³ *Total dust **Respirable fraction |
| REL (USA) | 10*; 5** mg/m ³ *Total dust **Respirable fraction |
| TLV (USA) | 10 mg/m ³ (e) |
| 7439-96-5 manganese | |
| PEL (USA) | Short-term value: C 5 mg/m ³ as Mn |
| REL (USA) | Short-term value: 3 mg/m ³ Long-term value: 1 mg/m ³ as Mn |
| TLV (USA) | 0.2 mg/m ³ as Mn |

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:** Wash hands before breaks and at the end of work.

· **Respiratory protection:** Use suitable respiratory protective device in case of insufficient ventilation.

· **Protection of hands:** Heat protection gloves

· **Material of gloves:** Leather gloves

· **Eye protection:**

Wear helmet or use face shield with filter lens. Provide protective screens and flash goggles, if necessary, to shield others. As a rule of thumb, start with a shade that is too dark to see the weld zone. Then go the next lighter shade which gives sufficient view of the weld zone.

· **Body protection:** Protective work clothing

CA

(Contd. on page 6)

**Safety data sheet**
according to 1907/2006/EC, Article 31

Printing date 04/17/2014

Version number 4

Revision: 11/20/2012

Trade name: UTP 6820 LC

(Contd. of page 5)

9 Physical and chemical properties· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

| | |
|---------|-----------|
| Form: | Solid |
| Colour: | Grey |
| Odour: | Odourless |

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Undetermined.

· **Flash point:** Not applicable.· **Self-igniting:** Product is not selfigniting.· **Danger of explosion:** Product does not present an explosion hazard.· **Density:** Not determined.· **Solubility in / Miscibility with water:**

Insoluble.

· **Solvent content:**

Solids content: 96.7 %

· **Other information** No further relevant information available.**10 Stability and reactivity**· **Reactivity**· **Chemical stability**· **Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

· **Possibility of hazardous reactions** No dangerous reactions known.· **Conditions to avoid** No further relevant information available.· **Incompatible materials:** No further relevant information available.· **Hazardous decomposition products:**

Welding fumes and gases cannot be classified simply. The composition and quantity of both are dependent upon the metal being welded, and the process, procedures, and electrodes used. Other conditions which also influence the composition and quantity of the fumes and gases to which workers may be exposed include: coatings on the metal being welded (such as paint, plating, galvanising, or phosphate coatings on steels which would produce phosphine gas), the number of welders and the volume of the work area, the quality and amount of ventilation, the position of the welder's head with respect to the fume plume as well as the presence of contaminants in the atmosphere (such as chlorinated hydrocarbon vapours from cleaning and degreasing activities which may be decomposed by the arc into toxic gases such as phosgene).

When the electrode is consumed, the fume and gas decomposition products generated are different in percent and form from the ingredients listed in SECTION II. Fume and gas decomposition products, and not the ingredients in the electrode are important. The concentration of a given fume or gas component may decrease or increase by many times the original concentration in the electrode. Also, new compounds not in the electrodes may form. Decomposition products of normal operation include those originating from the volatilization, reaction, or oxidation of the materials shown in SECTION II, plus those

(Contd. on page 7)

CA

**Safety data sheet**
according to 1907/2006/EC, Article 31

Printing date 04/17/2014

Version number 4

Revision: 11/20/2012

Trade name: UTP 6820 LC

(Contd. of page 6)

from the base metal and coating, etc..., as noted above. Reasonably expected fume constituents of this product would include: Example for Carbon dioxide shielded flux-cored electrode (AWS 5.20 E70-T-1): Reasonably expected fume constituents of this product would include: primarily oxides of Iron; secondarily complex oxides of Manganese, Silicon, Titanium and Sodium. The present ACGIH TLV for Manganese, 0.1 mg/m³ will result in a significant reduction from the 5 mg/m³ general welding fume (NOC) level. Example for Stainless Steel covered electrodes (AWS 5.4): Reasonably expected fume constituents of this product would include: primarily fluorides and complex oxides of Iron and Silicon, secondarily complex oxides of Manganese, titanium, chromium, nickel, sodium and potassium. The present OSHA PEL (Permissible Exposure Limit) - published in the U.S. Federal Register 71, pages: 10099-10385 - for hexavalent Chromium (Cr +6) is 0.005 mg/m³ which will result in a significant reduction from the 5 mg/m³ general welding fume (NOC) level. It applies to soluble chromates of the types found in covered stainless electrode fumes. Reasonably expected gaseous constituents would include Carbon monoxide and Carbon dioxide. Ozone and nitrogen oxides may be formed by the radiation from the arc. One recommended way to determine the composition and quantity of fumes and gases to which workers are exposed is to take an air sample from inside the welder's helmet if worn or in the worker's breathing zone. See ANSI/AWS F1.1 and ANSI/AWS F1.2-1992. In order to determine and evaluation of the existing problem areas, the standards prEn 15011 - part 1,4 can also be applied.

11 Toxicological Information

- Information on toxicological effects
- Acute toxicity:

- LD/LC50 values relevant for classification:

7440-02-0 nickel

Intraperitoneal LD50 250 mg/kg (rat)

- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:

Workers exposed to hexavalent chrome (Cr+6) are at an increased risk of developing lung cancer. It also possible that occupational exposure to (Cr+6) may result in asthma, and damage to the nasal epithelia and skin. To avoid any risk follow the requirements of the OSHA rule for hexavalent chromium published on February 28, 2006 in the U.S. Federal Register, pages:10099-10385 which established an 8-hour time-weighted average (TWA) exposure limit of 5 micrograms of hexavalent chrome per cubic meter of air (5 µg/m³). This is a considerable reduction from the previous PEL of 1 milligram per 10 cubic meters of air (1 mg/10 m³, or 100 µg/m³) reported as CrO₃, which is equivalent to a limit of 52 µg/m³ as (Cr+6)). This rule also contains ancillary provisions for worker protection such as requirements for exposure determination, preferred exposure control methods, including a compliance alternative for a small sector for which the new PEL is infeasible, respiratory protection, protective clothing and equipment, hygiene areas and practices, medical surveillance, recordkeeping, and start-up dates that include four years for the implementation of engineering controls to meet the PEL.

12 Ecological information

- Toxicity
- Aquatic toxicity: No further relevant information available.

(Contd. on page 8)

CA

**Safety data sheet**
according to 1907/2006/EC, Article 31

Printing date 04/17/2014

Version number 4

Revision: 11/20/2012

Trade name: UTP 6820 LC

(Contd. of page 7)

- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation** Must be specially treated adhering to official regulations.

European waste catalogue

12 01 13 welding wastes

12 01 20 spent grinding bodies and grinding materials containing dangerous substances

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport Information

- | | |
|---|--|
| • UN-Number | |
| • TDG, ADN, IMDG, IATA | Void |
| • UN proper shipping name | |
| • TDG, ADN, IMDG, IATA | Void |
| • Transport hazard class(es) | |
| • TDG, ADN, IMDG, IATA | |
| • Class | Void |
| • Packing group | |
| • TDG, IMDG, IATA | Void |
| • Environmental hazards: | |
| • Marine pollutant: | No |
| • Special precautions for user | Not applicable. |
| • Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | Not applicable. |
| • Transport/Additional information: | Not dangerous according to the above specifications. |

(Contd. on page 9)

CA



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04/17/2014

Version number 4

Revision: 11/20/2012

Trade name: UTP 6820 LC

(Contd. of page 8)

· **UN "Model Regulation":**

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Labelling according to EU guidelines:**
The product is not subject to identification regulations under EU Directives and the Ordinance on Hazardous Materials (German GefStoffV).
- **Hazard-determining components of labelling:**
nickel
- **Special labelling of certain preparations:**
Contains nickel, cobalt. May produce an allergic reaction.
- **National regulations:**
- **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department Issuing MSDS:** QS department
- **Contact:**
Mr. Bill Smith
phone +1- 905-564-0589
- **Abbreviations and acronyms:**
ICAO: International Civil Aviation Organization
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
Acute Tox. 4: Acute toxicity, Hazard Category 4
Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Carc. 1A: Carcinogenicity, Hazard Category 1A
- *** Data compared to the previous version altered.**

